



MANNOL Quad 4-Takt Racing 7807

A high-quality synthetic-based engine oil for modern high-load 4-stroke petrol- and diesel-powered engines of sports and utility terrain vehicles (quadracycles) with and without an integrated gearbox and with an oil bath clutch, with air and liquid cooling. It may be used in engines with a dry type clutch. It was designed for a guaranteed protection of the engine and the durability of the gearbox.

Product properties:

- A special additive package and a synthetic base ensure a high traction coefficient in friction elements that allow avoiding their wear due to the prevention of skidding and ensure an exact and smooth operation of the clutch during starting, acceleration and driving at a constant speed thus allowing an easy gear shift;
- It has excellent lubricating, antiwear and anti-scuffing properties that reduce fuel consumption, improve the power and service life of the engine. It provides a maximum wear protection of cylinder walls;
- It has an increased thermal oxidation stability and resistance to high temperatures, at which it preserves a strong oil film. It ensures easy cold starts in winter;
- Due to a high viscosity index, it preserves stable viscous properties at any operating conditions;
- Special detergent-dispersion additives maintain the engine parts ideally clean;
- It has excellent antifoam properties;
- High-performance inhibitors ensure excellent anticorrosion properties;
- It may be mixed with analogous mineral and synthetic oils;
- It is compatible with all exhaust control systems.

It was designed for petrol-powered 4-stroke engines of highway and off-road motorcycles, mopeds, all-terrain vehicles (quadracycles), scooters and other two-wheeled vehicles with a "wet" clutch complying with Euro I, II, III requirements where the required level of operating properties is API SL or lower and JASO MA/MA2.

It may be used in diesel-powered engines with a required level of operating properties API CF or lower.

Comply with the manufacturer's instructions provided in the user's manual of the engine, especially the oil replacement age!

SAE 10W-40
API SL/CF
JASO MA/MA2

PACKAGING

10L

MN7807-10

1000L	MN7807-IBC		
208L	MN7807-DR	Drum	
20L	MN7807-20	Plastic	