



CHEMPIOIL



9104 TRUCK CH-4 SHPD SUPER

Universal truck engine oil

> **Meets the requirements:**

SAE 15W-40, API CI-4/CH-4/SL, ACEA E7, A3/B4, JASO DH-1, GLOBAL DHD-1, VOLVO VDS-3, MAN M 3275, MB 228.3, MTU DDC Type 2, MACK EO-N/EO-M Plus, RENAULT RLD-2, CUMMINS CES 20076/77/78, CATERPILLAR ECF-2/ECF-1-a, DETROIT DIESEL PGOS 93K215, DEUTZ DQC-III-05

> **Volume:**

10L, 20L, 60L, 208L, 1000L

> **Product Characteristics:**

| Test | Method | Unit | Result |
|---------------------|--------|-------------------|--------|
| SAE-class | | | 15W-40 |
| Density at 15 °C | D 1298 | kg/m ³ | 890 |
| Viscosity at 40 °C | D 445 | Cst | 94,50 |
| Viscosity at 100 °C | D 445 | Cst | 14,15 |
| Viscosity at -20 °C | D 5293 | CP | 6231 |
| Viscosity index | D 2270 | | 154 |
| Flash point COC | D 92 | °C | 226 |
| Pour point | D 97 | °C | -42 |
| TBN | D 2896 | gKOH/kg | 11,03 |

ENGINE OIL